The TruView PSP and Film Positioning Device produces images of high diagnostic quality with a minimal number of exposures. It is both easy to use and to teach to auxiliary staff.



The TruView PSP and Film Positioning Device was created by Sydney Australia endodontist Dr Steven Cohn. Clinicians familiar with the original and popular Snapex radiography system also designed by Dr. Cohn will find the same friendly features with the TruView device.

The TruView is indicated for all phosphor plate and film systems in every clinical situation including endodontic working images with rubber dam.

The TruView consists of four components. All of the components may be autoclaved (Fig 1).

- 1 Phosphor plate/film holder for all anterior & posterior images.
- 1 Aiming ring.
- 1 90° angle rod used for parallel technique images.
- 1 105° angle rod used for the modified paralleling technique in the maxillary posterior area & for all posterior endodontic images.

# Fig 1

## CLINICAL USAGE

Maxillary anteriors with the paralleling technique. Use the straight portion of either rod to align the aiming ring (Fias 2 & 3).



Fig 2



Fig 3

Mandibular anteriors. The film or phosphor plate can be in the same plane (Fig 4) or at 90 degrees to the holder (Fig 5). With a narrow arch size 0 is suggested for comfort and to avoid a distorted image.





# Posterior images

For correct alignment the aiming rod and ring are always set up on the same side as the film or sensor (Figs 6 and 7)



Only two set ups are necessary for all posterior images. For example, when the maxillary right set up is rotated 180 degrees it will be correct for the mandibular left (Figs 8 and 9)





Fig 9

For posterior images the extension of the biting table always faces the patient's cheek (Figs 10-11). This is particularly important for **endodontic images** to allow the holder to fit around the rubber dam clamp (Figs 12-13).







Fig 11



Fig 12



For endodontic films use the triple cotton roll to allow space

for the file handles. The Ostby rubber dam frame, pictured, is

recommended. The rubber dam can be partially removed to

For all posterior images the patient must close firmly on the film holder. The holder must be parallel to the occlusal plane to achieve a complete & accurate image. Use single or multiple cotton rolls between the film holder and the opposing

teeth to correct for major occlusal discrepancies (Fig 14).

Three cotton rolls held together with autoclave tape forming a triple cotton roll is recommended.

the midline creating a "window" in the rubber dam and allow-

ing an unobstructed view of the file handles when aligning the Truview (Fig 15).

Fia 14

The fixed position of the film holder allows for accurate horizontal and vertical angulation changes using the same reference point that can be repeated during treatment or in the future to assess the results of endodontic and implant procedures, etc (Figs 16-18).

Fia 15



Fia 16 No horizontal shift



Fia 17 Mesial horizontal shift



Fia 18 Distal horizontal shift





One Dental Pty Ltd Unit 8 / 9 Packard Avenue Castle Hill NSW Australia 2154 P: (02) 9634 3443 F: (02) 9634 8661 E: sales@onedental.com.au



# Recommended cleaning and sterilization procedures for the TruView PSP and Film Positioning Device

- 1. Disinfect hands. Put on disposable gloves and proper protective gear. Disassemble the device. Inspect for any damage. Transport to the designated area for instrument cleaning, disinfecting and sterilizing.
- 2. Remove debris from components by manual cleaning with the aid of an ultrasonic machine and/or mechanically clean using an automated washer disinfector.
- 3. Inspect components for cleanliness and function. Put components in sterilization pouches. Plastic parts must be in a separate pouch and not touch metal instruments or other materials to avoid melting, warping or staining.
- 4. Place all the components in the steriliser following the manufacturer's Instructions for use. Sterilise as per the Australian Standard requirements of 134-136 degrees C for a minimum of 3 minutes.

DO NOT use phenol-based glutaraldehyde.

DO NOT CHEMICLAVE or DRY-HEAT STERILIZE.

DO NOT cold sterilize.

Note: Plastic parts have a limited life and should be replaced periodically. Any method of sterilization will shorten the life of plastic parts.

Australian Dental Association Guidelines for Infection Control (Ed. 3) 2015 pages 16 and 32 AS/NZS 4187:2014 Reprocessing of reusable medical devices in health service organisations. AS/NZS 4815:2016 Office-based health care facilities – Reprocessing of reusable medical and surgical instruments and equipment, and maintenance of the associated environment.